



Fotec AG

Phone:

e-mail:

Eigenheimstr. 22 CH-8700 Küsnacht

P.O.Box 1123 Switzerland

+41 44 913 30 00 Fax: +41 44 910 45 25

[info@fotec.ch](mailto:info@fotec.ch)

[www.fotec.ch](http://www.fotec.ch)

TECHNICAL INFORMATION

Küsnacht, February 2010

## **FOTECOAT 1069**

**standard version (see also  
Technical Information 1069)**

## **FOTECOAT 1069 HV**

**extra high viscosity**

## **FOTECOAT 1069 FAST**

**shorter exposure; for CtS**

***Dual cure solvent- and water resistant diazo emulsions.***

### **1. Description for all 3 FOTECOAT**

- Blue colour.
- High solids content.
- Post-exposure improves resistance.
- Stencil removal with usual decoaters is possible regardless of the high water resistance.
- The chemical hardening with FOTECHEM 2100 or 2130 is possible.

### **2. Hints for each version**

- FOTECOAT 1069 standard has a medium viscosity and high flexibility and is therefore ideal for plastisols, glass decoration and printing with abrasive inks.
- FOTECOAT 1069 HV has an extra high viscosity and can be used on coarse mesh in combination with an above-average stencil thickness.
- FOTECOAT 1069 FAST has a shorter exposure time than FOTECOAT 1069 Standard.

### **3. Storing**

- Unsensitized at 18-25°C: 1 year
- Sensitized at 20-25°C: 1 month
- Pre-coated screens stored  
in complete darkness at 20°C: 3 weeks

FOTEC AG

These Technical Informations are published without warranty. The results shown in these Technical Information are based on laboratory testing. The supplier declines any responsibility for incorrect use of these products which are manufactured and sold for industrial use only.