

# FOTECOAT SOLO

**FOTECOAT SOLO** is a line of presensitized, one component screen process emulsions.

**FOTECOAT SOLO** is ready to coat. Uniform viscosity. Less pinholes. No Diazo staining. Shelf-life up to 2 years.

**FOTECOAT SOLO** emulsions have different technical properties. They can be divided into application groups.

**Computer-to-Screen (CtS)** emulsions and the **DIR-EX SOLO** Line are available for solvents, water and combined inks.

## SOLVENT

### Solids

#### FOTECOAT 1811 SOLO

↓  
29% Magenta. Very economic

#### FOTECOAT 1850 SOLO

36% Grey-blue. Extra high definition

#### FOTECOAT 1860 SOLO

35% Blue, green and purple. Matt.  
Easy to decoat

## WATER

#### FOTECOAT 1836<sub>WR</sub> SOLO

35% Magenta. Short exposure time

#### FOTECOAT 1838 SOLO

38% Magenta. Add included diazo for longer print runs

## UV INKS

#### FOTECOAT 1855 UV

61% Blue. Medium viscosity.  
Coat 1x print side

## TRANSFER

#### FOTECOAT 1834 SOLO

40% Light green. Water resistant

#### FOTECOAT 1840 SOLO

41% Light green. Solvent resistant.

## THICK STENCILS

#### FOTECOAT 1835 SOLO

58% Purple. Extra high viscosity. WR

#### FOTECOAT 1837 SOLO

52% Rosa. Very high viscosity. WR

#### FOTECOAT 1845 SOLO

49% Blue. Very high viscosity. SR

#### FOTECOAT 1846 SOLO

44% Blue. High viscosity. SR

#### FOTECOAT 1847 SOLO

42% Blue. Viscous. SR

## PROJECTION

#### FOTECOAT 1884 SR

24% Light blue. Solvent resistant

#### FOTECOAT 1884 WR

35% Light blue. Water resistant.

**FOTEC AG**, POB 1123, Eigenheimstrasse 22, CH-8700 Küsnacht  
TEL+41 (0)44 913 30 00 FAX +41(0)44 910 45 25 Switzerland  
e-mail: info@fotec.ch Internet: www.fotec.ch

Edition: 9 2/2011